



# DAMPLOCK™

## CONCRETE WATERPROOFING PAINT

SEAL-KRETE® DAMPLOCK™ Concrete Waterproofing Paint is a ready-to-use, ultra low odor formula for concrete and masonry. Suitable for above and below grade use, DAMPLOCK waterproofing paint withstands up to 20 psi of hydrostatic pressure – meeting the ASTM standard for below grade waterproofing. It reduces radon gas penetration through basement walls and is ideal for use on concrete and cinder blocks, retaining walls, bird baths, pre-cast fixtures and foundations. **Important:** Read all directions thoroughly. Always wear gloves and eye protection.

**SURFACE PREP:** New concrete must have cured for a minimum of 30 days. The surface should be clean, sound and free of dirt, dust, oil, wax and grease. DAMPLOCK may be used on painted surfaces to improve water resistance; however, surface must be bare concrete for waterproofing.

**Cleaning:** Remove mold/mildew with a solution of 1 part bleach, 3 parts water. Rinse: let dry. Remove efflorescence with a wire brush and solution of 1 part muriatic acid, 4 parts water. Neutralize acid with a solution of baking soda and water (i.e., 1 lb. baking soda, 5 gallons of water). Rinse thoroughly: let dry.

**Repairs:** Repair surface breaks around wall/floor joints and patch cracks with DAMPLOCK Fast-Setting Hydraulic Cement or DAMPLOCK Concrete & Masonry Crack Filler, using trowel to smooth patch to surrounding area.

**APPLICATION:** Read "LIMITATIONS" section before use. Ready-to-use; do not dilute. Stir thoroughly before (and occasionally during) use. DAMPLOCK may be applied to a damp surface; however, application to a dry surface provides best results. Apply first coat with a 1/2" to 3/4" nap roller cover or high quality, nylon-polyester brush. Use a brush to work paint into the grout lines. Allow to dry 3 hours, then apply second coat. A minimum of 2 coats is recommended. **Note:** If leak occurs after applying 2 coats, pin holes may be present. Paint these areas again, using a brush to work paint into the pores.

**COVERAGE:** 75-125 sq.ft. per gallon, depending on surface porosity. Second coat coverage is approximately 50% greater.

**DRY TIME:** Dries in 2-3 hours, depending on temperature and humidity.

**TINTING:** May be tinted with universal colorants, up to 2 fl.oz. per gallon.

**CLEAN-UP & STORAGE:** Clean tools immediately after use with soap and water. Keep product from freezing.

**LIMITATIONS:** Use only when air and surface temperatures are 55-90°F. Do not apply if rain is forecast within 24 hours. Do not use on horizontal surfaces.

**CAUTION: KEEP OUT OF REACH OF CHILDREN. DO NOT TAKE INTERNALLY.** May cause eye and skin irritation. Avoid breathing vapors or spray mist. Open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air or wear respiratory protection (NIOSH/MSHA TC 23C or equivalent) or leave the area. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after use.

**FIRST AID: Eye Contact:** Flush thoroughly with water for at least 15 minutes. If irritation persists get medical attention. **If Inhaled:** If affected by vapors or spray mist, move to fresh air. If breathing difficulty continues, get medical attention. **If Swallowed:** Drink 2 glasses of water. Get immediate medical attention.



Color No. 101  
Bright White

**STOPS UP TO 20 PSI WATER PRESSURE**



PRODUCT NO.	UNIT	UPC CODE	CARTON QTY	CARTON BAR CODE	CARTON SIZE (L X W X H)	CARTON CUBIC FT	CARTON WT (LBS)	CARTONS / PALLET
101001	1 GALLON	0 15944 10101 6	4	9 00 15944 10101 3	14 x 14 x 8	.91	55	45 CASES
101005	5 GALLONS	0 15944 10105 8	1	---	---	---	66.5	36 UNITS



**STOPS UP TO 20 PSI WATER PRESSURE • LOCKS OUT WATER-GUARANTEED!\***  
**RESISTS MOLD & MILDEW GROWTH • REDUCES RADON GAS PENETRATION • IDEAL FOR BELOW-GRADE MASONRY**

