



# STUCCO-GUARD™

## ONE COAT FADE RESISTANT SEALER

**Seal-Krete® Stucco-Guard™** is a premium, low lustre, water-based acrylic sealer that provides a tough, flexible water-resistant film for new or aged stucco surfaces. Designed to penetrate deep into stucco pores, Stucco-Guard provides protection against color bleeding, premature fading, and mold and mildew growth. Ideal for hurricane/storm-prone areas Seal-Krete Stucco-Guard stops wind-driven rain (up to 124 mph) and helps prevent weather damage from freeze/thaw cycles when applied according to specification. Stucco-Guard binds chalky surfaces and improves the adhesion of paint and topcoats.

**Important:** Read all directions thoroughly. Always wear gloves and eye protection.

### Surface Prep

The surface must be clean and dry. Remove any loose or peeling paint and excessive chalk. Repair all cracks and surface breaks. Cover windows, doors, etc. prior to application. Use caution when applying on windy days, and immediately remove overspray with water.

For more information on surface prep, visit [www.seal-krete.com](http://www.seal-krete.com)

### Application

Read "LIMITATIONS" section before use. Stucco-Guard is ready to use, do not dilute. Prior to use, gently stir product with a stick for 30 seconds. Apply 1 coat of Stucco-Guard using a garden sprayer, airless sprayer, brush or roller (up to 1/2" nap). Spray applications should be backrolled after application to assure complete surface penetration. Stucco-Guard goes on milky white to visually aid in ensuring total coverage, but dries to a clear, low-lustre finish.

**To prime new, high pH stucco:** Apply a minimum of two flood coats, allowing a minimum of 2 hours dry time between coats. Stucco pH will be lowered, and surface can be painted after 5 days.

**Wind-driven rain protection:** Apply 2 flood coats and backroll to ensure complete surface penetration.

**Topcoating:** Stucco-Guard can be topcoated when dry with latex, oil-based or elastomeric coatings.

**Coverage:** 80-300 sq. ft. per gallon, depending on surface porosity and texture. Coverage on painted stucco is approximately 150 sq. ft. per gallon.

Second coat coverage is approximately 50% that of first coat.

**Dry Time:** 2-4 hours. Dry time will be longer in cool temperatures or high humidity environments.

**Clean-Up & Storage:** Clean tools with soap and water immediately after use. Store product in a dry area above 32° F.

Wait 30 days before cleaning sealed surface with a mild soap and water solution.

**Limitations:** Do not put in paint shaker, or shake vigorously.

Do not apply if rain is expected within 12 hours. Do not use if temperatures below 50° F are expected within 24 hours of application. Do not apply below grade.

**Caution:** Keep out of reach of children. Do not take internally.

### First Aid

**Eye Contact:** Flush with water for 15 minutes. **Skin Contact:** Prolonged contact may cause irritation. Wash affected area with soap and water. **If Swallowed:** Induce vomiting and seek immediate medical attention. **Inhalation:** If headache or nausea is experienced, remove the individual to fresh air. If symptoms persist, seek medical attention.



Product No.	Unit	UPC Code	Carton Qty.	Carton Bar Code	Carton size (L x W x H)	Carton size cubic ft. / lbs.	Cartons / Pallets
150001	1 GALLON	0 15944 15001 8	4	9 00 15944 15001 1	14 x 14 x 8	.91 / 39	45 CASES



**PROTECTS NEW or PAINTED STUCCO**  
**Excellent Primer • Revitalizes Color • Low Odor • Low VOC**



# STUCCO-GUARD™

## ONE COAT FADE RESISTANT SEALER

### Properties

- Meets ASTM E-514 for wind-driven rain (up to 124 mph)
- Non-yellowing
- Applies white, dries clear
- Improves paint adhesion
- Low-lustre finish
- Reduces cracking
- Enhances color
- Revitalizes old stucco surfaces
- Binds chalky surfaces
- Reduces efflorescence
- Resists mold and mildew growth
- Premium acrylic formula
- VOCs less than 100 g per liter
- Ultra low odor
- Complies with California air pollution regulations

### Technical Service:

For more information, technical assistance or to obtain a Material Safety Data Sheet, visit our website at [www.seal-krete.com](http://www.seal-krete.com), email us at [tech@seal-krete.com](mailto:tech@seal-krete.com) or call our technical service department at (800) 323-7357, M-F, 8am-5pm EST.

### Warranty:

A limited 5-year warranty is available on the quality and performance of this product on a per job basis. For full details on this warranty program, contact our technical service department. Otherwise, manufacturer/seller makes no warranty of any kind, except that this product is free from defect and is of merchantable quality. Buyer remedy for breach of warranty is limited to replacement of product or refund of purchase price.

**Warning!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log onto [www.epa.gov/lead](http://www.epa.gov/lead).



Binds chalky surfaces



Easy to apply—  
goes on white, dries clear.

