



# WET-LOOK

## CONCRETE/MASONRY SEALER

**SEAL-KRETE® Wet-Look Sealer** provides long-lasting surface protection, beauty and easy maintenance to a wide range of masonry and concrete surfaces. It protects against moisture damage while enhancing the natural color of brick, slate, stone and similar surfaces. The acrylic polymer resin technology is environmentally friendly, has very low odor and is easy to use. The non-yellowing formula dries to a clear, semi-gloss to high-gloss finish depending on surface porosity and the amount of product applied.

**Important:** Read all directions thoroughly. Wear gloves and eye protection.

**SURFACE PREP:** Surface must be clean, dry and oil-free (remove oil stains with a degreaser or SEAL-KRETE OSR oil stain remover). Make sure all curing compounds and releasing agents have been removed. Repair cracks and surface breaks. Cover windows, doors, etc., before application and use caution when applying on windy days. **Note:** Do not apply to concrete that has not cured for at least 30 days.

**For new or smooth concrete,** acid etching and neutralization are required for proper adhesion. Use a 1:3 solution of muriatic acid and water or SEAL-KRETE Clean-N-Etch and follow product directions. For complete procedure visit our web site.

**APPLICATION:** Read “LIMITATIONS” section before use. This sealer is ready-to-use; do not dilute. Stir but DO NOT SHAKE (shaking can create air bubbles which affect finish). Apply one coat with a garden sprayer or roller. Do not apply more than two coats. **Note:** Sealer appears milky white during application but dries to a clear finish.

**Garden sprayer:** lightly spray surface with a fan-tip spray pattern, then backroll to aid penetration and eliminate puddling. Remove overspray immediately with water.

**Roller:** dampen a short-nap (1/4"-3/8") roller with water, remove excess, then saturate with sealer. Roll onto surface keeping a wet edge to avoid streaks. Do not allow to puddle, foam or run.

**COVERAGE:** 150-300 sq.ft. per gallon (varies based on surface porosity). Second coat coverage is 50% greater.

**DRY TIME:** Dry to touch in 1 hour, recoat in 2 hours, allow foot traffic in 24 hours, vehicular traffic in 72 hours (77°F, 50% RH).

**CLEAN-UP & STORAGE:** Clean all tools immediately after use with soap and water. Store unused product in a dry place above 50°F. Do not use solvent-based cleaners on surface; clean occasionally with a mild soap and water solution.

**LIMITATIONS:** Do not apply to non-porous surfaces such as glazed tile or marble. Do not apply if rain is expected within 24 hours or if temperatures fall below 55°F within 24 hours of application. In rainy/icy conditions, surfaces can become slippery. To increase slip-resistance, add a non-skid additive (like SEAL-KRETE Clear Grip) to sealer before application.

**CAUTION: KEEP OUT OF REACH OF CHILDREN.**

**FIRST AID: For Eye Contact:** Flush with water for 15 minutes. **For Skin Contact:** Prolonged contact may cause irritation. Wash affected area with soap and water. **If Swallowed:** Induce vomiting and seek immediate medical attention. **If Inhaled:** If headache or nausea is experienced, remove the individual to fresh air. If symptoms persist, seek medical attention.

**LIMITED WARRANTY:** Manufacturer/seller makes no warranty of any kind except that this product is free from defect and is of merchantable quality. Buyer remedy for breach of warranty is limited to replacement of product or refund of purchase price.



PRODUCT NUMBER	UNIT SIZE	UPC CODE	CARTON QTY	CARTON CODE	CARTON SIZE (L X W X H)	CARTON SIZE (CUBIC FEET/LBS)	CARTON WT (lbs).	PALLET QTY. (CARTONS)
601001	1 GALLON	0 15944 60101 5	4	9 00 15944 60101 5	15 x 9.5 x 12.5	1.03	36	36
601005	5 GALLONS	0 15944 60105 3	1	N/A	12 x 12 x 15	1.25	44	36



**SEALS & PROTECTS EXPOSED AGGREGATE, SLATE, BRICK, STONE, CONCRETE, PRECAST PAVERS & MORE**  
**ENRICHES NATURAL COLOR • PROVIDES EASY MAINTENANCE • GREAT GLOSS RETENTION • MAXIMUM DURABILITY**

- Clear
- Interior / Exterior
- Very Low Odor
- Water Based
- Acrylic Formula
- OTC-compliant
- For Use on Bare Surfaces:
  - Concrete
  - Brick Pavers
  - Cobblestone
  - Slate
  - Stone
  - Stamped Concrete

**LIQUID PROPERTIES**

Solids: 30%

Proprietary Acrylic Resin

Water Based

Odor: Low

Appearance: Milky White, Dries Clear

VOC: Less than 100 grams per liter

**COVERAGE GUIDELINES**

	Material Coverage Approx. sq.ft./gal.
Brick	150
Smooth Concrete	300
Broom-finished Concrete	200
Stamped Concrete	200
Stone	300
Slate	250
Precast Pavers	175
Cobblestone	300
Exposed Aggregate	300
<b>FLOOR-TEX</b> ® Textured Coating	300

Note: Actual coverage will vary depending on porosity of surface.



*Provides a  
long-lasting  
“Wet Look”  
protective finish.*



**IMPROVED – NOW URETHANE FORTIFIED  
GREAT FOR PAVERS!**