



# Concrete Colors

## Low Lustre Sealer

**Seal-Krete® Concrete Colors Low Lustre Sealer** is a ready-to-use, matte finish sealer that penetrates deeply to seal and protect stained or bare concrete. It applies milky white and dries to a clear matte finish, enhancing the natural character of your surface and extending the life of newly stained finishes. Low Lustre Sealer is a durable, urethane-fortified acrylic formula with low odor and low VOCs, so it's easy to work with and safe for the environment. It has excellent chemical resistance and repels stains, making it ideal for pool decks, patios, porches, driveways, garages or anywhere you want to protect and beautify your concrete surface.

### SURFACE PREP

Note: *Proper surface prep is critical to product performance. A poorly prepared surface will repel the product.*

**Important:** Read all directions thoroughly. Always wear gloves and eye protection.

**Bare Concrete:** Concrete must have cured for a minimum of 30 days. Etch smooth-finished concrete (such as basements or garage floors) with a concrete etching solution (Seal-Krete Clean-n-Etch®). Remove any oil or petroleum based stains with a degreaser (Seal-Krete OSR®). If etching with muriatic acid, the area must be neutralized before proceeding.

**Stained or Painted Surfaces:** Freshly stained surfaces must have cured for a minimum of 24 hours. Previously painted or stained surfaces must be sound and free from blistering or peeling paints and coatings. Clean with a solution of TSP and water, rinse and allow to dry.

For more information on surface prep, visit [www.SEAL-KRETE.com](http://www.SEAL-KRETE.com)

### APPLICATION

Read "LIMITATIONS" section before use. Concrete Colors Low Lustre Sealer is ready to use, do not dilute. Stir gently, do not shake. Apply in light, even coats. One coat is recommended, but extra coats may be applied for increased surface durability or sheen level. Note: Sealer applies milky white, but dries clear.

**Roller Application:** Use a 1/4" nap roller for smooth surfaces, or a 3/8" nap for rough or porous surfaces. Dampen roller, remove excess water, then saturate roller with product. Keep a wet edge while rolling. Do not allow sealer to puddle, foam or run.

**Pump Sprayer:** Set at a fine spray and apply using a circular motion. To eliminate puddling, or for a more uniform finish, backroll immediately after spraying.

**Coverage:** 150-500 sq. ft. per gallon, depending on surface porosity and texture.

**Dry Time** (77° F, 50% relative humidity): Dry to touch in 1 hour. Recoat in 2 hours. Light foot traffic, 24 hours. Heavy foot traffic, furniture placement, or vehicle traffic, 72 hours. Dry time will be longer in cool temperatures or high humidity environments.

**Clean-Up & Storage:** Clean tools with soap and water immediately after use. Store product in a dry area above 32° F.

**Limitations:** Use only when temperature is 50-90° F and will not fall below 50° F within 24 hours of application. Do not apply if rain is expected within 24 hours. Do not use over solvent-based (oil-based) epoxy paints. Do not use on glazed tile. Do not use in areas subject to hydrostatic pressure. Smooth finished concrete may be slippery when wet. Try using an anti-skid additive (like Seal-Krete Clear Grip®) for added safety in high foot-traffic areas.

**Caution: Keep out of reach of children. Do not take internally.**

### FIRST AID

**Eye Contact:** Flush with water for 15 minutes. **Skin Contact:** Prolonged contact may cause irritation. Wash affected area with soap and water. **If Swallowed:** Induce vomiting and seek immediate medical attention. **Inhalation:** If headache or nausea is experienced, remove the individual to fresh air. If symptoms persist, seek medical attention.



Product	No.	Size	UPC Code	Case Bar Code	Carton Size (L x W x H)	Carton Size (cubic ft / lbs)	Carton Qty	Pallet Qty
Low-Lustre Sealer	360001	1 gallon	0 15944 36001 1	9 00 15944 36001 4	14 x 14 x 8	.91 / 39	4	45 cases



**PROTECTIVE FINISH FOR CONCRETE STAINS**  
**UV RESISTANT • RESISTS MILDEW • ENHANCES COLOR**



# Concrete Colors Low Lustre Sealer

## FEATURES

- Seals and protects stained or bare concrete
- Seals in color
- Extends the life of stained concrete
- Reduces pockmarking and cracking
- Clear finish won't yellow
- Low odor
- Resists chlorine, salt, chemicals and UV rays
- Premium, urethane-fortified acrylic formula

## LIQUID PROPERTIES

- Solids: 10%
- Proprietary Urethane Acrylic Resin
- Water-Based
- Odor: Low
- Appearance: Milky White Liquid, Dries Clear
- VOC: Less than 50 g/L

## TECHNICAL SUPPORT

For more information, technical assistance or to obtain a Material Safety Data Sheet, visit our website or call our technical service department M-F, 8am-5pm EST at (800) 323-7357, or visit our website at [www.seal-krete.com](http://www.seal-krete.com).

**WARRANTY:** Manufacturer/seller makes no warranty of any kind except that this product is free from defect and is of merchantable quality. Buyer remedy for breach of warranty is limited to replacement of product or refund of purchase price.

**WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log onto [www.epa.gov/lead](http://www.epa.gov/lead).

